
KERN SXS100K-2L







| Measuring system | |
|---|----------------------|
| Adjustment options: | External calibration |
| Eccentric loading at 1/3 [Max]: | 500 mg |
| Linearity: | 30 g |
| Load cell connection: | 6-wire |
| Readability [d]: | 10 g |
| Recommended adjusting weight: | 150 kg (M1) |
| Repeatability: | 10 g |
| Resolution: | 15000 |
| Stabilisation time under laboratory conditions: | 2 s |
| Warm up time: | 30 min |
| Weighing capacity [Max]: | 150 kg |
| Weighing system: | Strain gauge |
| Weighing units: | oz kg g lb |

| Display digit height (large): | 5,500 cm | |
|---|----------|--|
| Counting | | |
| Counting resolution: | 30000 | |
| Mininum piece weight at piece counting (Laboratory: | 5 g | |
| Mininum piece weight at piece counting (Normal): | 50 g | |

Display

| Functions | | |
|--|-----|--|
| Counting function: | yes | |
| PRE-TARE function: | yes | |
| Vibration-free weighing (Animal weighing program): | yes | |
| Weighing with tolerance range: | yes | |

| Environmental conditions | |
|--------------------------------|--------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -10 °C |
| Minimum humidity: | 0 % |
| | |

| 1 Ower suppry | |
|---------------------------------|------------------------|
| Charging time: | 12 h |
| Input voltage: | 220 V - 240 V AC 50 Hz |
| Mains adapter/adapter included: | EURO |
| Operating time (Backlight off): | 80 h |
| Operating time (Backlight on): | 40 h |

| Services (optional) | | |
|---|---------|--|
| Adjustment at the location of installation: 961-249 | | |
| DAkkS Certificate: | 963-129 | |

| Category | |
|----------------|------------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Industiral scale |
| | |

| Packaging & shipping | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 600 x 930 x 245 mm |
| Gross weight: | 36,100 kg |
| Net weight: | 33,500 kg |
| Shipping method: | Parcel service |

| Construction | |
|---------------------------------------|--------------------|
| Cable length of display device: | 2,500 m |
| Dimensions of display device (WxDxH): | 232 x 150 x 80 mm |
| Dimensions of weighing plate (WxDxH): | 650 x 500 x 135 mm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Revolving screw feet: | yes |
| Wall mount: | yes |
| Weighing surface (WxD): | 650 x 500 mm |

KERN SXS100K-2L



Stainless steel platform scale with stainless steel IP68 display and EC type approval [M]

