

KERN SXC 60K-3

Interlinked for industry of the future: Stainless steel platform scale with up to four data interfaces and optional alibi memory



Approval

CE mark ✓

Display

Display type LCD
 Display type LCD with backlight
 Display screen size 160×60 mm
 Display backlight ✓
 Display digit height 48 mm
 Languages of the user interface English
 Symbol language

Construction

Dimension display device (W×D×H) 232×150×80 mm
 Dimensions weighing platform (W×D×H) 400×300×123 mm
 Material display housing stainless steel
 Material weighing plate stainless steel
 Material platform Stainless steel
 Dimensions weighing surface (W×D) 300×300 mm
 Cable length 3 m
 Display device cable length 3 m
 Allowed cable length display device [Max] 20 m
 Material load cell(s) Stainless steels
 Load cells - number 1
 Levelling feet adjustable ✓
 Wall mount ✓

Functions

Number of keys for operation 7
 Auto-off interval(s) in mains power mode off
 Auto-off interval(s) in battery mode/rechargeable battery mode 5 min
 2 min
 1 min
 30 min
 60 min
 30 sec
 Capacity - Display ✓
 PreTare function ✓
 Tare function manual (multi)
 Hold function ✓
 Percentage determination ✓
 Counting function ✓
 Tolerance weighing ✓

Category

Brand KERN
 Product category Industrial scale
 Product group Stainless steel platform scale
 Product family SXC

Measuring System

Construction type of the scale Single-range balance
 Number of weighing ranges 1
 Weighing system Strain gauge
 Weighing capacity [Max] 60 kg
 Readability [d] 0,005 kg
 Resolution 12.000
 Linearity ± 0,015 kg
 Reproducibility 0,005 kg
 Default unit kg

kg
 g
 lb
 ffa
 PCS
 %

Adjustment options Adjusting with external weight
 Recommended adjusting weight 60 kg (M1)
 Stabilization time 3 s
 Warm-up time 30 min
 Eccentric loading at 1/3 [Max] 0,025 kg
 Maximum creep (15 minutes) 20 g
 Maximum creep (30 minutes) 40 g
 Loadcell type stainless steel IP68 encapsulated
 Load cell connection 6-wire

KERN SXC 60K-3



Interlinked for industry of the future: Stainless steel platform scale with up to four data interfaces and optional alibi memory

Tolerance weighing - type of signal	acoustically visual
Function for averaging under unstable weighing conditions	✓
Recipe/summing level	Sum A
Sum memory function	✓
Alibi memory	optional internal memory
Alibi memory - number of memory spaces	250.000

Interfaces	RS-232 (optional, factory)
	Ethernet (optional, factory)
	WiFi (optional, factory)
	Alibi memory (optional, factory)
	analogue (0 - 10 V) (optional, factory)
	analogue (4 - 20 mA) (optional, factory)
	Bluetooth BLE (v4.0) (optional, factory)
	USB-Device (optional, factory)

IP protection - complete device	-
IP protection - display	IP68
IP protection - load cell	IP68
IP protection - platform	no IP protection

Counting	
Smallest piece weight when piece counting - laboratory conditions	2 g
Smallest piece weight when piece counting - normal conditions	20 g
Counting reference weight can be entered	✓
Reference quantity	5, 10, 20, 50, n (any number of pieces)
Counting resolution (laboratory conditions)	30.000

Power Supply	
Input voltage power supply / power [Max]	110 V - 240 V AC
Plug-in power supply type	Built-in power supply
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO
Rechargeable battery optional	Rchrg. battery optional - intern

Rechargeable battery charging time	8 h
Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	48 h
Battery	no battery
Battery / accumulator type	Li-Ion

Environmental conditions	
Humidity of environment [Min]	0 %
Humidity of environment [Max]	80 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C

Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	800×465×230 mm
Net weight	11,1 kg
Shipping method	Parcel service
Net weight approx.	12 kg
Gross weight approx.	14 kg
Shipping weight	17,1 kg

Services (optional)	
Article number for adjustment at the location of installation	961-249
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

KERN SXC 60K-3



Interlinked for industry of the future: Stainless steel platform scale with up to four data interfaces and optional alibi memory

Pictograms

STANDARD



OPTION



FACTORY

